



Stilren takarmatur för belysning i korridorer, trapphus, kontor, konferensrum och övriga allmänna utrymmen.

Utförande: Naturanodiserad aluminium, natur, mörkgrå- eller bronslackerad. Bländskydd av prismatic akryl.

Montage: Dikt tak.

Anslutning: Snabbkopplingsplint, D108 mm 3x4mm² . D400 mm 5x4mm², överkopplingsbar.

Design: Per Sundstedt.

W	D/MM	KG	ART
1x40W/2Gx13	400	3,4	7408-3-XX
1x40W/2Gx13	400	3,4	7408-3-XXHFF
1x55W/2Gx13	400	3,4	7409-3-XX
1x55W/2Gx13	400	3,4	7409-3-XXHFF
LED/1800LM*	400	3,3	7407-3-XX
LED/1800LM*	400	3,3	7407-3-XXHFF
LED/2600LM*	400	3,3	7429-3-XX
LED/2600LM*	400	3,3	7429-3-XXHFF

Med inbyggd närvarosensor/With built in motion detector

LED/1800LM*	400	3,3	7407-3-XXS
LED/1800LM*	400	3,3	7407-3-XXHFFS
LED/2600LM*	400	3,3	7429-3-XXS
LED/2600LM*	400	3,3	7429-3-XXHFFS

Med nödljus 1h/With emergency light 1h

LED/1800LM*	400	3,3	7407-3-XXE
LED/1800LM*	400	3,3	7407-3-XXHFFE
LED/2600LM*	400	3,3	7429-3-XXE
LED/2600LM*	400	3,3	7429-3-XXHFFE

XX = Färg/Color -38 Aluminium, -97 Brons/Bronze, -98 Mörkgrå/Dark grey.

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

LED* se www.zero.se för uppdaterad teknisk information gällande Led.

LED* visit www.zero.se for updated technical information regarding LEDs.

TILLBEHÖR/ACCESSORIES

Närvarosensor till 7408/7409/Motion detector to 7408/7409 **98900-1-01**

Finish: Anodized aluminium, natural, bronze or dark grey painted and white painted steel. Diffuser in prismatic acrylic.

Installation: Ceiling-installation.

Connection: Terminal block. D108 mm 3x4mm² . D400 mm 5x4mm², two entry holes.

Design: Per Sundstedt.

