



Arcad pendel kan bestyckas med upp till 4x42W kompaktlysrör, vilket ger ett mycket bra allmänljus. Vajerlängd justeras vid montage.

**Utförande:** Mörkgrå strukturlack. Skärm av matt opalglas alt. matt akryl.

**Montage:** Pendlad från tak i vajer.

**Anslutning:** Snabbkopplingsplint 5x4mm<sup>2</sup>. Överkopplingsbar.

**Design:** Per Sundstedt.

W	SKÄRM/SHADE	KG	ART
4x18W/Gx24q-2	Glas/Glass	9	4042-3-21HF
4x18W/Gx24q-2	Akryll/Acrylic	6,4	4042-3-27HF
4x26-42W/Gx24q-3	Glas/Glass	9	4043-3-21HF
4x26-42W/Gx24q-3	Akryll/Acrylic	6,4	4043-3-27HF
4x32W/Gx24q-3	Glas/Glass	9	4045-3-21HFF
4x32W/Gx24q-3	Akryll/Acrylic	6,4	4045-3-27HFF
4x42W/Gx24q-3	Glas/Glass	9	4046-3-21HFF
4x42W/Gx24q-3	Akryll/Acrylic	6,4	4046-3-27HFF
4xE27/max 53W	Glas/Glass	9,2	4044-3-21
4xE27/max 53W	Akryll/Acrylic	6,2	4044-3-27

HFF = Dimmbar med DALI, DSI, SwitchDim




HFF = Dimmable with DALI, DSI, SwitchDim

**Finish:** Dark grey painted steel. Shade in matt opal glass or matt acrylic.

**Installation:** Ceiling, wire pendant.

**Connection:** Snap-in terminal block 5x4mm<sup>2</sup>. Two entry holes and knockout for external mains cable.

**Design:** Per Sundstedt.



TAK/CEILING 30-31



VÄGG/WALL 130-132