



Downlight för belysning av konferensrum, korridorer, entréhallar mm.

Utförande: Vitlackerad metall. Matt optiskt glas. Bländskydd av opal akryl ovan glas är standard till storlek 1000 mm. Finns som tillbehör till storlek 330 och 500.

Montage: Infäld i ventilerat alt. oventilerat undertak.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: Per Sundstedt.

W	D	KG	ART
2x24W/2G10	330	3,1	7400-1-01HF
2x24W/2G10	330	3,1	7400-1-01HFF
4x24W/2G10	500	6,3	7400-3-01HF
4x24W/2G10	500	6,3	7400-3-01HFF
6x36W/2G11	1000	23,9	7400-5-01HF
6x36W/2G11	1000	23,9	7400-5-01HFF
LED*	330	3,1	7404-1-01
LED*	330	3,1	7404-1-01HFF
LED*	500	6,3	7404-3-01
LED*	500	6,3	7404-3-01HFF

Med inbyggd närvarosensor/With built in motion detector

LED*	330	3,1	7404-1-01S
LED*	330	3,1	7404-1-01HFFS
LED*	500	6,3	7404-3-01S
LED*	500	6,3	7404-3-01HFFS

Med nödljus/With emergency light

LED*	330	3,1	7404-1-01E
LED*	330	3,1	7404-1-01HFFE
LED*	500	6,3	7404-3-01E
LED*	500	6,3	7404-3-01HFFE

HFF = Dimmbar - DALI, DSI, SwitchDim.
HFF = Dimmable with DALI, DSI, SwitchDim

LED* se www.zero.se för teknisk information gällande Led.

LED* visit www.zero.se for technical information regarding LEDs.

TILLBEHÖR/ACCESSORIES	ART
Opal akryl bländskydd 330/Opal acrylic diffuser.	97401-1-27
Opal akryl bländskydd 500/Opal acrylic diffuser.	97401-3-27
Montageplåt mjuka tak 330/Support-frame for soft ceilings	97400-1-01
Montageplåt mjuka tak 500/Support-frame for soft ceilings	97400-3-01
Montageplåt mjuka tak 1000/Support-frame for soft ceilings	97400-5-01

Finish: White painted steel. Matt optical glass. Diffuser in opal acrylic above glass is standard for size 1000 mm, available as accessory for sizes 330 och 500.

Installation: Recessed.

Connection: Snap-in terminal block 5x4mm². Two entry holes.

Design: Per Sundstedt.

