



**Utförande:** Vit-, svart- eller rödlackerad (NCS 1580-Y90R) aluminium och metall samt matt akryl. Skärmen kan vridas och vinklas.  
**LED info:** 14W/1008LM/3000K/4 SDCM.  
**Montage:** Dikt tak med pendelrör. Andra längder på begäran.  
**Anslutning:** Kopplingsplint 5x4 mm2. Överkopplingsbar.  
**Design:** Johan Carpner 2010.

W	H/MM	ART
26-42W/Gx24q	500	8150-1-XX
42W/Gx24q	500	8150-1-XXHFF
26-42W/Gx24q	800	8150-3-XX
42W/Gx24q	800	8150-3-XXHFF
26-42W/Gx24q	1100	8150-5-XX
42W/Gx24q	1100	8150-5-XXHFF
LED 1008LM	500	8151-1-XX
LED 1008LM	500	8151-1-XXHFF
LED 1008LM	800	8151-3-XX
LED 1008LM	800	8151-3-XXHFF
LED 1008LM	1100	8151-5-XX
LED 1008LM	1100	8151-5-XXHFF

XX = Färg. -01 vit, -06 svart, -07 röd.

HFF = Dimmbar med DALI, DSI, SwitchDim

HFF = Dimmable with DALI, DSI, SwitchDim

**Finish:** White-, black- or red (NCS 1580-Y90R) painted aluminum and metal.  
Adjustable shade for indirect light.

**Installation:** Ceiling with pendant tube. Other lengths possible on request.

**LED info:** 14W/1008LM/3000K/4 SDCM.

**Connection:** Terminal block 5x4 mm2 Two entry holes.

**Design:** Johan Carpner 2010.



