



Lampstandard with dynamic reflector which refracts the light away from critical dazzle glare angles with great precision. You have to be in the immediate vicinity of the lampshade to see it fully illuminated. At a distance, the lampshade only gives a gentle light and thus indicates its position.



Finish: Black or grey painted aluminium. Shade in acrylic.

Installation: On standard pole D108 mm, 3000-4000 mm above ground.

Connection: Terminal block 4x10mm².

Design: Per Sundstedt

With patented dynamical diffuser. Patent no. 9902727-8



Stolparmatnr med dynamisk avbländning som med stor exakthet bryter bort ljuset från bländningskritiska vinklar. För att uppleva armaturen helt upplöst måste man befinna sig i dess direkta närområde. På håll lyser armaturen bara svagt och markerar därmed bara sin position.

Utförande: Svart alt. grålackerad aluminium. Kupa av UV-stabil akryl. Med dynamisk avbländning.

Montage: Monteras på standardstolpe 3000-4000 mm över mark. Stolpfäste D108mm. Stolpe finns som tillbehör. Fundament tillhandahålls ej av Zero.

Anslutning: Via säkringsinsats 4x10mm² i stolpe.

Design: Per Sundstedt

Med patenterad dynamisk avbländning. Patent nr. 9902727-8

W	FÄRG/FINISH	ART NR
57W/Gx24q-5	Svart/Black	3216-1-06
57W/Gx24q-5	Grå/Grey	3216-1-10
35W/E27/ME	Svart/Black	3376-1-06
35W/E27/ME	Grå/Grey	3376-1-10
70W/ME/E27	Svart/Black	3213-1-06*
70W/ME/E27	Grå/Grey	3213-1-10*
70W/SE/E27**	Svart/Black	3214-1-06*
70W/SE/E27**	Grå/Grey	3214-1-10*
LED 2055 Lumen/33W	Svart/Black	3219-1-06
LED 2055 Lumen/33W	Grå/Grey	3219-1-10
** = För ljuskälla med tändspänning max 2,3 kV.		
** = For lamp with ignition voltage max 2,3 kV		
TILLBEHÖR/ACCESSORIES	ART NR	
Svartlackerad stolpe 3-4m/Black pole 3-4m	93210-1-06	
Grålackerad stolpe 3-4m/Grey pole 3-4m	93210-1-10	

