

Bowi ger ett effektivt och mjukt ljus genom den vita tygskärmen. Fungerar lika bra på kontoret som i övriga allmänna utrymmen.

**Utförande:** Vitlackerad metall. Flamskyddat tyg Kvadrat Palet 2. Tvättbar 60°. Vid glödljusutförande är duken perforerad och vid lysrör tät.

**Montage:** Dikt tak.

**Anslutning:** Snabbkopplingsplint 5x4mm<sup>2</sup>. Överkopplingsbar.

**Design:** Per Sundstedt.

W	MM	KG	ART
2x36W/2G11	1000	5,2	3130-1-39HF
2x36W/2G11	1000	5,2	3130-1-39HFF
4x36W/2G11	1000	5,5	3131-1-39HF
4x36W/2G11	1000	5,5	3131-1-39HFF
4xE14	800	5,1	3132-1-39

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

TILLBEHÖR/ACCESSORIES	L/MM	ART
Undertaksprofil/Support for soft ceiling	600	93130-1-01
Undertaksprofil/Support for soft ceiling	1200	93130-3-01

**Finish:** White painted steel. Fire protected fabric Kvadrat Palet 2. Washable 60°. Art no. 3132-1-39 has perforated fabric.

**Installation:** Ceiling-installation.

**Connection:** Snap-in terminal block 5x4mm<sup>2</sup>. Two cable entries.

**Design:** Per Sundstedt.

