



Utförande: Lackerad aluminium. Vit, svart, rödorange RAL 040 50 70 alt. grå RAL 000 50 00 alt. beige/paper RAL 1011. Bländskydd av opal akryl. Skrämen är vridbar.

LED info: 20W/1509LM/3000K/4SDCM/RA80

Montage: Pendlad i 2 m vajer.

Anslutning: 2,5 m kabel med stickpropp, vid HFF utan stickpropp.

Design: TAF 2014.

W	FÄRG/FINISH	ART.
LED 1509LM	Vit/White	8315-3-01
LED 1509LM	Vit/White	8315-3-01HFF
LED 1509LM	Svart/Black	8315-3-06
LED 1509LM	Svart/Black	8315-3-06HFF
LED 1509LM	Rödorange/Redorange	8315-3-07
LED 1509LM	Rödorange/Redorange	8315-3-07HFF
LED 1509LM	Beige/Beige	8315-3-49
LED 1509LM	Beige/Beige	8315-3-49HFF
LED 1509LM	Grå/Grey	8315-3-95
LED 1509LM	Grå/Grey	8315-3-95HFF

HFF = Dimmbart/Dimmable DALI, SwitchDim, DSI.

Finish: Painted aluminium. White, black, redorange RAL 040 50 70 or grey RAL 000 50 00. Diffuser in opal acrylic. The shade is turnable.

LED info: 20W/1509LM/3000K/4SDCM/CRI80

Installation: In ceiling, 2 meter wire.

Connection: 2,5 m cable with plug, when HFF without plug.

Design: TAF 2014

