



**Utförande:** Oljad alt. svartbetsad ekfanér. Bländskydd av matt akryl, vid metallhalogen klart täckglas Kan även tillverkas i andra träslag och ytbehandlingar på begäran. Finns med ett flertal olika ljuskällor.

**Montage:** Dikt tak.

**Anslutning:** Snabbkopplingsplint 5x4mm<sup>2</sup>. Överkopplingsbar.

**Design:** Fredrik Mattson 2010.

W	FÄRG/FINISH	ART
26-32W/Gx24q	Oljad ek/Oiled oak	8000-1-32
26-32W/Gx24q	Svart ek/Black oak	8000-1-36
32W/Gx24q	Oljad ek/Oiled oak	8000-1-32HFF
32W/Gx24q	Svart ek/Black oak	8000-1-36HFF
35W/G12	Oljad ek/Oiled oak	8001-1-32
35W/G12	Svart ek/Black oak	8001-1-36
LED*	Oljad ek/Oiled oak	8002-1-32
LED*	Svart ek/Black oak	8002-1-36

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

LED\* se [www.zero.se](http://www.zero.se) för teknisk information gällande Led.




LED\* visit [www.zero.se](http://www.zero.se) for technical information regarding LEDs.

**Finish:** Oiled oak veneer natural or black stained. Matt acrylic diffuser. When metal halide clear glass. Available in other wood finishes and stains on request. Available with several light sources. 26-32W compact fluorescent, 35W metal halide and LED Philips Fortimo 2000 lumen.

**Installation:** Ceiling.

**Connection:** Terminal block 5x4mm<sup>2</sup>. Two entry holes.

**Design:** Fredrik Mattson 2010.



Andra spridningsvinklar på begäran.  
Other beam angles on request.

PENDLAR/PENDANTS 69

VÄGG/WALL 116-117

BORD/TABLE 148