

Utförande: Oljad alt. svartbetsad ekfanér. Bländskydd av matt akryl, vid metallhalogen klart täckglas Kan även tillverkas i andra träslag och ytbehandlingar på begäran. Finns med ett flertal olika ljuskällor.

Montage: Dikt tak alt. 3-fas strömskena eller på vägg.

Anslutning: 3-fas skena alt. snabbkopplingsplint 5x4mm², överkopplingsbar.

Design: Fredrik Mattson 2010.

TAK/VÄGG/CEILING/WALL

W	FÄRG/FINISH	ART.
26-32W/Gx24q	Oljad ek/Oiled oak	8010-1-32
26-32W/Gx24q	Svart ek/Black oak	8010-1-36
32W/Gx24q	Oljad ek/Oiled oak	8010-1-32HFF
32W/Gx24q	Svart ek/Black oak	8010-1-36HFF
35W/G12	Oljad ek/Oiled oak	8011-1-32
35W/G12	Svart ek/Black oak	8011-1-36
LED*	Oljad ek/Oiled oak	8012-1-32
LED*	Svart ek/Black oak	8012-1-36

MED 3-FAS ADAPTER/WITH 3-PHASE ADAPTER

W	FÄRG/FINISH	ART.
26-32W/Gx24q	Oljad ek/Oiled oak	8014-1-32
26-32W/Gx24q	Svart ek/Black oak	8014-1-36
35W/G12	Oljad ek/Oiled oak	8015-1-32
35W/G12	Svart ek/Black oak	8015-1-36
LED*	Oljad ek/Oiled oak	8016-1-32
LED*	Svart ek/Black oak	8016-1-36

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

LED* se www.zero.se för teknisk information gällande Led.





LED* visit www.zero.se for technical information regarding LEDs.

Finish: Oiled oak veneer natural or black stained. Matt acrylic diffuser. When metal halide clear glass. Available in other wood finishes and stains on request. Available with several light sources. 26-32W compact fluorescent, 35W metal halide and LED Philips Fortimo 2000 lumen.

Installation: Ceiling, wall or with 3-phase adapter.

Connection: 3 phase track or terminal block 5x4mm², two entry holes.

Design: Fredrik Mattson 2010.



Andra spridningsvinklar på begäran.
Other beam angles on request.

PENDLAR/PENDANTS 69

VÄGG/WALL 116-117

BORD/TABLE 148

