



Utförande: Stomme i vitlackerad aluminium. Kupa av matt opalglas. Skärm av sträckmetall, vit, svart eller koppar.

Montage: Dikt tak alt. vägg.

Anslutning: Snabbkopplingsplint 5x4mm².

Design: Joel Karlsson, Krook & Tjäder Design 2011.

W	FÄRG/FINISH	ART.
26-42W/Gx24q	Vit/White	8080-1-01
42W/Gx24q	Vit/White	8080-1-01HFF
26-42W/Gx24q	Svart/Black	8080-1-06
42W/Gx24q	Svart/Black	8080-1-06HFF
26-42W/Gx24q	Koppar/Copper	8080-1-78
42W/Gx24q	Koppar/Copper	8080-1-78HFF

HFF = Dimmbar - DALI, DSI, SwitchDim.

HFF = Dimmable with DALI, DSI, SwitchDim

TILLBEHÖR/ACCESSORY

Distans för utanpåliggande ledning **98080-1-01**

Distance for external mains

Finish: Base in white painted aluminium. Matt opal glass and shade in expanded metal, white, black or copper.

Installation: Ceiling or wall.

Connection: Terminal block 5x4mm².

Design: Joel Karlsson, Krook & Tjäder Design 2011.

