

DOT R

Omar Carraglia - Davide Groppi / 2015



A tool to light.

A luminaire designed for use with state-of-the-art LED modules to offer superior performance and a wide range of light beams.

Elemento di luce.

Un apparecchio illuminante progettato per utilizzare moduli a LED in grado di fornire prestazioni superiori ed un'ampia gamma di fasci luminosi.


DOT R

Omar Carraglia - Davide Groppi / 2015

Recessed / Direct / Indoor

Material	Metal		
Finish	.03 Matt White	.04 Matt Black	.49 Matt Black/Polished Gold

Note Recessed luminaire. Adjustable in all directions. Plasterboard hole: 40x40 mm. Minimum space for recessed installation: 60 mm. *Apparecchio illuminante da incasso. Orientabile in tutte le direzioni. Foro del cartongesso: 40x40 mm. Spazio minimo per incasso: 60 mm.*




DOT R

13W
Max 350mA DC
2700K / 3000K
CRI >97
Driver not included



Matt White - 2700K
Matt White - 3000K
Matt Black - 2700K
Matt Black - 3000K
Matt Black/Polished Gold - 2700K
Matt Black/Polished Gold - 3000K

1A4770300.27.20
1A4770300.30.20
1A4770400.27.20
1A4770400.30.20
1A4774900.27.20
1A4774900.30.20



DOT R 51

Max 10W - GU10
100-240V - 50/60Hz
ON/OFF
Bulb not included



Matt White - ON/OFF
Matt Black - ON/OFF
Matt Black/Polished Gold - ON/OFF

1A3700300.00.00
1A3700400.00.00
1A3704900.00.00


The sizes are expressed in millimeters.

Omar Carraglia - Davide Groppi / 2015


DOT R

Compulsory accessories / Accessori obbligatori


Drivers / Alimentatori



Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/17W(15W)/IP20/DALI	DOT R	1Z0241180.350	



Driver / Alimentatore				Not included
220-240V(100-127V)	350mA/18W(15W)/IP20/PUSH - 1-10V	DOT R	1Z0240870.350	



Driver / Alimentatore				Not included
220-240V	350mA/17W/IP20/TRIAC/IGBT	DOT R	1Z0240850.350	


Other accessories / Altri accessori




Lens / Lente				Not included
Beam - 14°	2700K - CRI >97 - 983lm	DOT R	1A3090000.00.00	
	3000K - CRI >97 - 1038lm			
Beam - 24°	2700K - CRI >97 - 943lm	DOT R	1A3100000.00.00	
	3000K - CRI >97 - 996lm			
Beam - 36°	2700K - CRI >97 - 955lm	DOT R	1A3110000.00.00	
	3000K - CRI >97 - 1005lm			
Beam - 50°	2700K - CRI >97 - 965lm	DOT R	1A3120000.00.00	
	3000K - CRI >97 - 1016lm			

Optional accessories / Accessori opzionali


Other accessories / Altri accessori




Accessory holder + Honeycomb louvre / Porta accessori + Frangiluce nido d'ape		Not included	
	DOT R	1X0080400.01.00	




Elliptical filter / Filtro ellittico		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.02.00



Blue filter / Filtro blu		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.03.00



Red filter / Filtro rosso		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.04.00



Yellow filter / Filtro giallo		Not included	
Standard	Compulsory with 1X0080400.01.00	DOT R	1X0080000.05.00

Optional accessories / Accessori opzionali

Bulbs / Lampadine



LED - GU10 - PAR16		Not included	
	220-240V - 5,5W - 25° 3000K - 375lm - CRI >97 Energy Efficiency G - Dimmable	DOT R 51	1Y0330500




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° 2700K - 390lm - CRI >95 Energy Efficiency G - Dimmable	DOT R 51	1Y1580210




LED SORAA - GU10 - MR16		Not included	
	230V - 7,5W - 10° 3000K - 410lm - CRI >95 Energy Efficiency G - Dimmable	DOT R 51	1Y1580010


Other accessories / Altri accessori



Darklight		Not included	
	LED SORAA - GU10 - MR16	DOT R 51	1Y1580040



25° beam filter / Filtro fascio 25°		Not included	
	LED SORAA - GU10 - MR16	DOT R 51	1Y1580020



36° beam filter / Filtro fascio 36°		Not included	
	LED SORAA - GU10 - MR16	DOT R 51	1Y1580030