
Compass

wall light



Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Photometric data and technical information	Page 3
5. Installation	Page 3
6. Ordering codes	Page 4
7. Certifications & standards	Page 6
8. Maintenance & Cleaning	Page 6

Versions



4073R
Page 4



4073S
Page 5

Compass

wall light

1. Product overview

Metallic reading wall light with a circular rotating head, designed for both reading and ambient lighting.

The head rotates up to 145° horizontally, providing either direct reading light or indirect ambient illumination.

In the recessed version, the canopy sits flush against the wall. Installation requires a Ø60 mm drill hole in drywall or headboard for the remote driver.



2. Finishes and Materials

26 Black

55 Beige

59 Terracotta

3. Light Source & Dimming

Lamping

LED 3W (Ang. 38° / >90 CRI / 350mA) 230V

2700K / Typ* 285 lumens

3000K / Typ* 367 lumens

*Integrated LED module (included).

Dimming options:

Standard: NON DIMMABLE


Optional: TRIAC, DALI, CASAMBI

Compass

wall light

4. Photometric Data and Technical Information

Photometric data corresponds to the output of each individual lamp.
Access to photometric files in download area.
2D / 3D / BIM Files available. Access to files in download area here.



5. Installation

Surface canopy



Recessed canopy with remote driver



 Ø 60 mm drill in
dropped ceiling

Compass

wall light

6. Ordering Codes

Lamping (Recessed Canopy 4073R)

LED 3W (Ang. 38° / >90 CRI / 350mA) 230V
 2700K / Typ* 285 lumens
 3000K / Typ* 367 lumens
 *Integrated LED module (included).

Finishes

26 Black
 55 Beige
 59 Terracotta



DIM: NON DIMMABLE (Optional: TRIAC, DALI, CASAMBI)

Drawing	Mounting	Finish Body	Ordering Code 2700K	Ordering Code 3000K
COM_4073R 	Recessed, Remote driver Ø 60 mm drill.	Black	COM_4073R_26W	COM_4073R_26M
		Beige	COM_4073R_55W	COM_4073R_55M
		Terracotta	COM_4073R_59W	COM_4073R_59M

Compass

wall light

6. Ordering Codes

Lamping (Surface Canopy 4073S)

LED 3W (Ang. 38° / >90 CRI / 350mA) 230V
 2700K / Typ* 285 lumens
 3000K / Typ* 367 lumens
 *Integrated LED module (included).

Finishes

26 Black
 55 Beige
 59 Terracotta



DIM: NON DIMMABLE (Optional: TRIAC, DALI, CASAMBI)

Drawing	Mounting	Finish Body	Ordering Code 2700K	Ordering Code 3000K
COM_4073S 	Surface mounted. Driver in the canopy.	Black	COM_4073S_26W	COM_4073S_26M
		Beige	COM_4073S_55W	COM_4073S_55M
		Terracotta	COM_4073S_59W	COM_4073S_59M

Compass

wall light

7. Certifications & Standards

2700K version   $\frac{IP}{20}$  

3000K version   $\frac{IP}{20}$  

Warranty: 2 years

100% made in Spain

8. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.