


Table Lamps | 220-240 V
2 topLED 20 W DC - 24 W AC | CRI 90
9585



Technical data	
Construction year	2021
Type	Table Lamps
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward and upward
Nominal power	20 W DC
Total Power	24 W
Source lumens	2290 lm
Nominal input voltage	220 - 240 V AC
Input voltage range	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI-2 - PUSH DIM
Directional	Swivelling
total angle (vertical plane)	360 °
total angle (horizontal plane)	360 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Electric socket	Type F
Cable length	2.5 m
Resin potting	No
Type of light emission	Double emission
Net weight	20.600 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	Aluminium
Colour	Anodised Black
Processing	Anodisation
Finishing diffuser	
Material	Glass
Colour	transparent
Finishing base	
Material	Iron
Colour	black
Processing	Coating

Table Lamps | 220-240 V | 2 topLED 20 W DC - 24 W AC | CRI 90 | Base 9585

Double emission table lamps for indoor application. The warm white LED light source with a diffused light distribution is composed of 2 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 2290 lm, with a 114.5 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a anodised black finish, processed by means of anodisation; the diffuser is made of glass. The ingress protection degree is IP20; the total weight is of 20.600 kg.

The total absorbed power is 24 W The power supply cable is included and features a 2.5 m length.

The device features protection class I and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 2 light sources of energy efficiency class F.

Illuminotechnical Features

Light Output Ratio (LOR)	74 %
Source lumens	2290 lm
Delivered lumens	1711 lm
Consumption	24 W
Luminaire efficacy	71 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C

LED Life / Failure Ratio

L70 B20 C0 72500h

