

Tik

bollard light



Table of contents

1. Product overview	Page 2
2. Finishes and materials	Page 2
3. Light Source & dimming	Page 2
4. Installation	Page 3
5. Photometric Data and Technical Information	Page 3
6. Ordering codes	Page 4
7. Certifications & standards	Page 5
8. Maintenance & Cleaning	Page 5

Versions



TIK_4098X
Page 4



TIK_4099X
Page 4

Tik

bollard light

1. Product overview

Metallic outdoor bollard light available in two heights: 494 mm and 804 mm. Features a PMMA lens diffuser (60° beam angle) and integrated LED, providing direct light. The cylindrical tube encloses the light source and is non-adjustable.

The remote driver must be installed in an IP65-rated box or indoors. Maximum cable length between driver and bollard: 17 meters. Double-layer coating ensures high resistance to corrosion and maritime environmental conditions.



2. Finishes and Materials



88 Grey Stone
96 Anthracite
89 Pale Green

3. Light Source & Dimming

Lamping

LED 6,2W (2700K / Ang. 60° / >90 CRI / 350mA) 230V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°.

*Integrated LED module (included).

Dimming options:

Standard: TRIAC

Optional: DALI

Tik

bollard light

4. Installation


Built-in driver for direct mains connection

Surface-mounted on a solid base (concrete or similar).
Not suitable for installation on soil or grass.



60° beam angle


Acrylic optic. It provides diffuse, uniform illumination and is visible as a decorative light line when viewed from the side.



5. Photometric Data and Technical Information

Photometric data corresponds to the output of each individual lamp.
Access to photometric files in download area.

2D / 3D / BIM Files available. Access to files in download area here.



Tik

bollard light

6. Ordering Codes

Lamping 4098X

LED 6,2W (2700K / Ang. 60° / >90 CRI / 350mA)
230V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°

DIM: TRIAC (Optional DALI)

Finishes:

88 Grey Stone

89 Pale Green

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4098X IP65 	Bollard light. Hard wired (no plug). Surface mounted on a solid base.	Outdoor	Grey Stone	TIK_4098X_88W
		Outdoor	Pale Green	TIK_4098X_89W
			Anthracite	TIK_4098X_96W

Lamping 4099X

LED 6,2W (2700K / Ang. 60° / >90 CRI / 350mA)
230V / Typ 725 lumens

Optic lens: (PMMA) lens diffuser 60°

DIM: Optional DALI

Finishes:

88 Grey Stone


89 Pale Green

96 Anthracite



Drawing	Mounting	Setting	Finish Body	Ordering Code
TIK_4099X IP65 	Bollard light. Hard wired (no plug). Surface mounted on a solid base.	Outdoor	Grey Stone	TIK_4099X_88W
		Outdoor	Pale Green	TIK_4099X_89W
			Anthracite	TIK_4099X_96W

7. Certifications & Standards



Warranty: 2 years
100% made in Spain

8. Maintenance & Cleaning

Our lighting fixtures are crafted with high-quality materials and finishes to ensure durability and timeless elegance. To maintain their original beauty, please follow these care recommendations:

1. Regular cleaning: Dust the fixture regularly using a soft, dry microfiber cloth to prevent buildup.
2. For deeper cleaning: If necessary, use a slightly damp cloth with clean water. Always dry the surface immediately with a dry cloth.
3. Avoid harsh products: Do not use alcohol, abrasive cleaners, solvents, or detergents, as they may damage the finish and alter the appearance.

In case of failure, LEDs can be easily replaced.