

DATASHEET

Type: **MONA SMALL**
Name: Table light
ID: PC950
Designed by: Lucie Koldová



Download

Description

The collection is a showcase of original design and refined combinations of materials, such as glass, metal, and wood. It features a tubular LED light source with a range of colour temperatures to choose from.

Tech. description

The light comprises a glass shade, metal body, and tubular LED light source with triplex opal glass diffuser. The glass shade and LED light source assembly are secured with dural endcaps. The electronics are housed in the body of the light.




Available colour options: <https://mbapi.cz/red/pis/eu/en/pc950>

CONSTRUCTION SPECIFICATION

Weight: 4 kg
Construction material: glass, metal
Cord length [mm]: 2,200 mm
Mounting: Table
Environment: Indoor

DIMENSIONS [mm]



ELECTRICAL SPECIFICATION

Input voltage [V]: 100 - 240 V
Frequency [Hz]: 50-60 Hz
Max. power [W]: 2.5 W
Coverage IP: 20
Socket: -
Light source: non-user replaceable LED module
Energy class: E

CERTIFICATIONS



BROKIS®

BROKIS S.R.O.
ŠPANIĚLOVA 1315/25
163 00 PRAHA 6 - ŘEPY
CZECH REPUBLIC

ORG ID 64940799
VAT ID CZ64940799
C 42174 MĚSTSKÝ SOUD
V PRAZE

TEL +420 567 211 517
TECHNICAL@BROKIS.CZ
INFO@BROKIS.CZ
WWW.BROKIS.CZ

2024_04

PAGE 1



CP14560 Complete LED source for MONA S - 2700 K, BLACK

Type	LED module
Lamp wattage [W]	2,5 W
Input voltage [V]	24 VDC
Energy class	E
Flux [lm]	106 lm
Light colour [K]	2700 K
CRI	90+
Lifespan [h]	20000h
Dimmable	yes (PWM)

CP14562 Complete LED source for MONA S - 4000 K, BLACK

Type	LED module
Lamp wattage [W]	2,5 W
Input voltage [V]	24 VDC
Energy class	E
Flux [lm]	117 lm
Light colour [K]	4000 K
CRI	90+
Lifespan [h]	20000h
Dimmable	yes (PWM)

CP14564 Complete LED source for MONA S - 5000 K, BLACK

Type	LED module
Lamp wattage [W]	2,5 W
Input voltage [V]	24 VDC
Energy class	E
Flux [lm]	125 lm
Light colour [K]	5000 K
CRI	90+
Lifespan [h]	20000h
Dimmable	yes (PWM)